



Sengol Exports

"Total Solution" from the Indian market



Some of our renowned public and private sector clients with whom we are registered and approved with are Major Refinery and Petroleum Companies, Indian Oil, Hindustan Petroleum, EIL, PDIL, MECON, CIDC, GWSSB, PHED, MJP, PMC, PCMC, APGENGO, HPCL, SAKAR SANKUL, LODHA, SAIL, and many others.

Sengol Exports
F 5 Civil Township Rourkela 769004 india
kausal.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market

Trunnion Mounted Ball Valve with Electrical Actuator




Size : 6" to 24"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT / GFT / TFM / PEEK
Pressure : 150# / 300# / 600# / 900#
Temp. : Upto 180 °C / 250 °C
Class : 150# / 300# / 600# / 900#
Ends : Flanged

Multi Port Design 3 Way / 4 Way / 5 Way Ball Valve with Electrical Actuator



Size : 1/2" to 12"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT / GFT / TFM / PEEK
Press. : 10 Kg/cm²
Temp. : Upto 180 °C / 250 °C
Class : 150# / 300#
Ends : Screwed / Flanged

Extended Stem Ball Valve for Cryogenic Application with Electrical Actuator



Size : 1/2" to 8"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PEEK / TFM / GFT / PTFE
Pressure : 150# / 300# / 600# / 900#
Temp. : - 40 to 180 °C
Class : 150# / 300# / 600# / 900#
Ends : Screwed / Flanged / TC End / Socket Weld

2 Way Ball Valve S/E - F/E with Electrical Actuator



Size : 1/2" to 12"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT / GFT / TFM / PEEK
Pressure : 150# / 300# / 600# / 900#
Temp. : Upto 180 °C / 250 °C
Class : 150# / 300# / 600# / 900#
Ends : Screwed / Flanged / TC End / Socket Weld

2 Way Wafer / Jacketed Type Ball Valve with Electrical Actuator



Size : 1/2" to 6"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT / GFT / TFM / PEEK
Pressure : 150#
Temp. : Upto 180 °C / 250 °C
Class : 150#
Ends : Wafer Type

2 Way V - Knotch Type Ball Valve with Electrical Actuator



Size : 1/2" to 16"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT / GFT / TFM / PEEK
Pressure : 150# / 300#
Temp. : Upto 180 °C / 250 °C
Class : 150# / 300#
Ends : Flanged

Flush Bottom Reduce Bore Ball Valve with Electrical Actuator



Size : 1" to 4"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT / GFT / TFM / PEEK
Pressure : 150#
Temp. : Upto 180 °C / 250 °C
Class : 150#
Ends : Flanged

PTFE (FEP - PFA) Lined Ball Valve with Electrical Actuator



Size : 1/2" to 8"
MOC : WCB / CF8 / CF8M / CF3M
Lining : FEP / PFA - STD. Thickness
Seals : PTFE / GFT / CFT
Pressure : 150#
Temp. : FEP 180 °C / PFA 230 °C
Class : 150#
Ends : Flanged

UPVC / Polypropylene (PP) Ball Valve with Electrical Actuator



Size : UPVC : 1/2" to 4" / PP : 1/2" to 12"
MOC : UPVC / PP
Seals : NBR
Pressure : 10 Kg/cm²
Temp. : Upto 80 °C
Ends : Socket / Screwed / Flanged

Sengol Exports

F 5 Civil Township Rourkela 769004 india

kausol.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market

Rubber Lined Wafer Type Butterfly Valve with Electrical Actuator



Size : 1.1/2" to 72"
MOC : CI / DI / WCB / CF8 / CF8M
Seals : Nitrile / NBR / EPDM / Viton
Pressure : PN 6, 10, 16, 20 & 25
Temp. : -20 °C to 80 °C (Depending On MOC)
Ends : Wafer Type

Rubber Lined Wafer Type Double Flange Butterfly Valve with Electrical Actuator



Size : 3" to 72"
MOC : CI / DI / WCB / CF8 / CF8M
Seals : Nitrile / NBR / EPDM / Viton
Pressure : PN 6, 10, 16, 20 & 25
Temp. : -20 °C to 80 °C (Depending On MOC)
Ends : Wafer Type / Double Flange

PTFE (FEP - PFA) Lined Butterfly Valve with Electrical Actuator



Size : 2" to 20"
MOC : WCB / CF8 / CF8M / CF3M
Lining : FEP / PFA - STD. Thickness
Seals : FEP / PFA
Pressure : 10 Kg/cm²
Temp. : FEP 180 °C / PFA 230 °C
Ends : Wafer Type / Double Flange / Lug Type

High Performance Butterfly Valve Spherical Disc Valve with Electrical Actuator



Size : 1.1/2" to 24"
MOC : WCB / CF8 / CF8M / CF3M
Seals : NBR / PTFE / RPTFE / EPDM / VITON
Pressure : PN 6 / 10 / 16 / 20 & 25
Temp. : Upto 180 °C / 250 °C
Ends : Wafer Type / Double Flange / Lug Type

Double Off - Set Disc Butterfly Valve with Electrical Actuator



Size : 2.1/2" to 88"
MOC : WCB / CF8 / CF8M / CF3M
Seals : NBR / PTFE / RPTFE / EPDM / VITON
Pressure : PN 10 / 16 / 20 & 25
Temp. : Upto 180 °C / 250 °C
Ends : Wafer Type / Double Flange

Extended Stem Butterfly Valve with Electrical Actuator



Size : 1.1/2" to 88"
MOC : WCB / CF8 / CF8M / CF3M
Seals : NBR / PTFE / RPTFE / EPDM / VITON
Pressure : PN 10 / 16 / 20 & 25
Temp. : Upto 180 °C / 250 °C
Ends : Wafer Type / Double Flange

Triple Offset Disc Butterfly Valve with Electrical Actuator



Size : 2" to 36"
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / GFT / CFT
Pressure : PN 6 / 10 / 16 / 20 & 25
Temp. : Upto 180 °C / 250 °C
Ends : Wafer Type / Double Flange / Lug Type

Aluminium Butterfly Valve with Electrical Actuator



Size : 1.1/2" to 12"
MOC : Aluminium Alloy
Seals : Nitrile / NBR / EPDM / Viton
Pressure : PN 10 / 16
Temp. : Upto 180 °C
Ends : Wafer Type

UPVC Body Butterfly Valve with Electrical Actuator



Size : 1.1/2" to 12"
MOC : UPVC / PP
Seals : NBR / EPDM
Pressure : Upto 10 Kg/cm²
Temp. : Upto 180 °C
Ends : Wafer Type

Fabricated Double Flange Damper Valve with Electrical Actuator



Size : 1.1/2" to 88"
MOC : IS Grade MS / S.Steel
Seals : Nitrile / NBR / EPDM / Viton
Pressure : Upto 10000 MMWC / PN 6 / PN 10 (Depending On Requirement)
Temp. : -20 °C to 500 °C
Ends : Double Flange

Multi Louver Damper Valve with Electrical Actuator



Size : 3000MM X 3000MM
MOC : IS Grade MS / S. Steel
Louvers : Aluminium / MS S. Steel
Pressure : Upto 10000 MMWC / PN 6 / PN 10 (Depending On Requirement)
Temp. : -20 °C to 500 °C
Ends : Wafer Type

Guillotine Damper Valve with Electrical Actuator



Size : 3000MM X 3000MM
MOC : IS Grade MS / S. Steel
Pressure : Upto 10000 MMWC / PN 6 / PN 10 (Depending On Requirement)
Temp. : -20 °C to 500 °C
Ends : Flanged / Wafer

Sengol Exports

F 5 Civil Township Rourkela 769004 india

kausal.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market

Foot Mounted Electrical Actuator with Linkage Arm for ID Fan Damper



Torque : 35NM to 32000NM **Arm** : WCB / S. Steel
Supply : 220V AC & 415V AC **Foot Bracket** : WCB / S. Steel
 (Other On Requirement)

AWWA C504 Standard Larger Diameter Butterfly Valve with Electrical Actuator



Size : 1.1/2" to 104"
MOC : IS Grade MS / WCB / CF8
Seals : NBR / EPDM / Nitrile / Viton
Pressure : PN 6, 10, 16, 20 & 25
Temp. : -20 °C to 180 °C
 (Depending on MOC)
Ends : Double Flange
 AWWA C 207

High Pressure Globe Control Valve with Electrical Actuator



Size : 1/2" to 12"
MOC : WCC / CF8M / Duplex
Seals : Metal to Metal / PTFE
Pressure : 150#, 300#, 600#
 900#, 1500#, 2500#
Temp. : 180 °C to 450 °C
Class : 150#, 300#, 600#
 900#, 1500#, 2500#
Ends : Flanged / But Weld

2 Way & 3 Way Globe Control Valve with Electrical Actuator



Size : 1/2" to 12"
MOC : WCB / CF8 / CF8M
Seals : Metal to Metal / PTFE
Pressure : 150# / 300# / 600#
 900#
Temp. : Upto 180 °C / 450 °C
Class : 150# / 300# / 600#
 900#
Ends : Flanged / Socket Weld

Knife Gate Valve with Electrical Actuator



Size : 1/2" to 24"
MOC : CI / WCB / CF8 / CF8M
Press. : 150#, 300#
 (Above On Req.)
Ends : Lugged / Flanged / Butt Weld

Pinch Valve with Electrical Actuator



Size : 2" to 12"
MOC : CI / WCB / CF8
Seals : CF8M
Pressure : NBR / EPDM
Temp. : Upto 10 Kg/cm²
 Upto 80 °C
Ends : Flanged



COM Series Electrical Actuator for Combustion application

Torque : 100 kg-cm to 1200 kg-cm
Supply : 220, 110V AC / 24V DC
Travel : 90° (Quarter Turn)
Application : Oil Fired Burner / Furnace Control, Damper Actuation, Chiller Valves of ACR with Thermostat, AHU, Cooling Tower



High Torque Electrical Actuator

Torque : 6000NM to 65000NM
Supply : 220, 110V AC / 24V DC 415V AC / 380V AC
Travel : 90° (Quarter Turn)
Application : Blower Actuation, Damper Actuation, Higher size Butterfly Valve



Spare Worm Gear Box for Electrical Actuator

Torque : 300NM to 65000NM
MOC : Ductile Iron / Gun Metal / Aluminium Bronze
Travel : 90° (Quarter Turn)
Application : Ball Valve, Butterfly Valve & Damper Actuation



Spare Bevel Gear Box for Electrical Actuator

Torque : 150NM to 3500NM
MOC : Ductile Iron / Gun Metal / Aluminium Bronze
Travel : Linear - Multi Turn
Application : Gate Valve, Globe Valve, Guillotine Damper Valve

Sengol Exports

F 5 Civil Township Rourkela 769004 india
kausal.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market




UTILITY & PROCESS LINES BALL VALVES

<p>2 Way Ball Valve S/E - F/E</p>  <p>Size : 1/2" to 12" Model : QB1 MOC : CI/ WCB / CF8 / CF8M Seals : PTFE / CFT/ GFT/TFM/ PEEK Pressure : 150# / 300# / 600# / 900# Temp. : Upto 180°C / 250°C Class : 150# Ends : Screwed / Flanged / Socket / Triclover Type</p>	<p>Multi Port Design 3 & 4 Way Ball Valve</p>  <p>Size : 1/2" to 12" Model : COK MOC : WCB / CF8 / CF8M Seals : PTFE / CFT/ GFT/ TFM/ PEEK Pressure : 150# / 300# / 600# / 900# Temp. : Upto 180°C / 250°C Class : 150# / 300# Ends : Screwed / Flanged / Socket / Triclover Type</p>	<p>Extended stem Ball Valve for Low Temperature</p>  <p>Size : 1/2" to 8" Model : QB3 MOC : WCB / CF8 / CF8M Seals : PTFE / CFT/ GFT/ TFM/ PEEK Pressure : 150# / 300# / 600# / 900# Temp. : -20°C TO 180°C Class : 150# Ends : Screwed / Flanged / Socket</p>
---	---	--

FLOW CONTROLLING LINES BALL VALVES

<p>Jacketed Ball Valve</p>  <p>Size : 1/2" to 4" Model : QB4 MOC : WCB / CF8 / CF8M Ball Port : 30° / 60° / 90° V Curve Seals : PTFE / CFT/ GFT/ TFM/ PEEK Pressure : 150# / 300# Temp. : Upto 180 °C / 250 °C Class : 150# / 300# Ends : Flanged End</p>	<p>High Pressure Ball Valves 3000WOG</p>  <p>Size : 1/2" to 2" Model : QB5 MOC : CF8 / CF8M Seals : PTFE / CFT/ PEEK Pressure : Upto 200 Kg/Cm² Temp. : 80°C Ends : Screwed Type</p>	<p>V Knotch Ball Valve - Basis weight Valve</p>  <p>Size : 1/2" to 4" Model : QB6 MOC : WCB / CF8 / CF8M Ball Port : 30° / 60° / 90° V Curve Seals : PTFE / CFT/ GFT/ TFM/ PEEK Pressure : 150# / 300# Temp. : Upto 180°C / 250°C Class : 150# / 300# Ends : Flanged End</p>
--	--	---

SPECIAL APPLICATION BALL VALVES

<p>Plug Valve Lubricated Soft Seated</p>  <p>Size : 1/2" to 8" Model : QB7 MOC : WCB / CF8 / CF8M Seals : PTFE / CFT/ GFT Pressure : 150# Temp. : FEP - 180°C / PFA - 230°C Class : 150# Ends : Flanged Type</p>	<p>Metal Seated Ball Valve for High Temperature Application</p>  <p>Size : 1/2" to 8" Model : QB8 MOC : WCB / CF8 / CF8M Ball : Tunston / Std. Stellite Coated Seals : Metal Seat (Stellite Coated) Pressure : 150# Temp. : FEP - 180°C PFA - 230°C Class : 150# Ends : Flanged Type</p>	<p>Flush Bottom Reduce Bore Ball Valve</p>  <p>Size : 6"X8" / 8"X10" / 10"X12" / 12"X14" Model : QB9 MOC : WCB / CF8 / CF8M Seals : PTFE / CFT/ GFT / TFM/ PEEK Pressure : 150# Temp. : Upto 180°C 250°C Class : 150# Ends : Flanged Type</p>
--	--	---

FLOW CONTROLLING BUTTERFLY VALVE

<p>Tripple Offset Butterfly Valve</p>  <p>Size : 1.1/2" to 36" Model : QF6 MOC : WCB / CF8 / CF8M / CF3M Seals : PTFE / CFT/ GFT Pressure : PN6, 10, 16, 20 & PN25 Temp. : Upto 180°C / 250°C Ends : Wafer Type / Double Flanged</p>	<p>Aluminium Body Butterfly valve (Kitz Type)</p>  <p>Size : 1.1/2" to 12" Model : QF7 MOC : Aluminium Alloy Lining : Nitrile / NBR/ EPDM Pressure : PN 10 / 16 Temp. : Upto 180°C Ends : Wafer type</p>	<p>Cement Butterfly Valve (WAM Type)</p>  <p>Size : 4" to 16" Model : CF8 MOC : Alluminium Alloy / WCB Seals : NBR Pressure : Upto 6kg / Cm² Temp. : Upto 80°C Ends : Single Flange / Double Flange</p>
--	--	---

Sengol Exports

F 5 Civil Township Rourkela 769004 india
kausal.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market

UTILITY LINES BUTTERFLY VALVE

Rubber Lined Wafer type Butterfly Valve



Size : 1, 1/2" to 72"
Model : QF1
MOC : CI/ DI/ WCB / CF8 / CF8M
Seals : Nitrile / NBR/ EPDM / Viton
Pressure : PN6, 10, 16, 20 & PN25
Temp. : -20°C to 180°C (Depending on MOC)
Ends : Wafer Type

Rubber Lined Double Flanged Butterfly Valve



Size : 3" to 72"
Model : QF2
MOC : CI/ DI/ WCB / CF8 / CF8M
Seals : Nitrile / NBR/ EPDM / Viton
Pressure : PN6, 10, 16, 20 & PN25
Temp. : -20°C to 180°C (Depending on MOC)
Ends : Wafer Type / Double Flanged

PTFE (FEP-PFA) Lined 2 Piece Design Butterfly Valve



Size : 1, 1/2" to 20"
Model : QF3
MOC : WCB / CF8 / CF8M / CF3M
Seals : FEP / PFA
Pressure : Upto 10 Kg/cm²
Temp. : FEP 180°C / PFA 250°C
Ends : Wafer Type

PROCESS LINE BUTTERFLY VALVE

High Performance Butterfly valve



Size : 1, 1/2" to 24"
Model : QF4
MOC : WCB / CF8 / CF8M / CF3M
Seals : PTFE / CFT/ GFT
Pressure : PN6, 10, 16, 20 & PN25
Temp. : Upto 180°C / 250°C
Ends : Wafer Type

Pharma / Food Butterfly Valve



Size : 2" to 16"
Model : CF9 ITC
MOC : CI/WCB / CF8 / CF8M
Seals : PTFE (TEFLON)
Pressure : PN6, 10
Temp. : Upto 180°C
Ends : Wafer Type


Extended stem Butterfly Valve



Size : 1, 1/2" to 88"
Model : CF5
MOC : CI/WCB / CF8 / CF8M
Seals : Nitrile / NBR / EPDM/ Viton
Pressure : PN6, 10, 16, 20 & PN25
Temp. : Upto 180°C / 250°C
Ends : Wafer Type / Double Flanged


DAMPER VALVE

Fabricated Double Flange Butterfly Valve



Size : 1, 1/2" to 88"
MOC : IS Grade MS / S.Steel
Seals : Nitrile / NBR/ EPDM / Viton
Pressure : Upto 10000MMWC / PN 6 / PN 10 (Depending on REQ.)
Temp. : -20° to 500°C
Ends : Double Flanged

Damper Butterfly Valve



Size : Upto 3000MM x 3000MM
MOC : IS Grade MS / S.Steel
Pressure : Upto 10000MMWC / PN 6 / PN 10 (Depending on REQ.)
Temp. : -20° to 500°C
Ends : Flanged / Wafer

Multi Louver Damper



Size : Upto 3000MM x 3000MM
MOC : IS Grade MS / S.Steel
Louvers : Aluminum / MS / S.Steel
Pressure : Upto 10000MMWC / PN 6 / PN 10 (Depending on REQ.)
Temp. : -20° to 500°C
Ends : Flanged / Wafer

GATE VALVE - GLOBE VALVE - PISTON VALVE

Resilient Gate Valve



Size : 1 1/2" to 48"
MOC : GGG40
Seals : EPDM
Pressure : PN 16 / PN 10 (Depending on Req.)
Temp. : -20° to 80°C
Ends : Flanged as per BS / DIN

IC Globe Valve - Soft Seated



Size : 1/2" to 4"
MOC : CF8 / CF8M
Seals : PTFE / CFT
Pressure : 150#
Temp. : -20°C to 180°C
Ends : Screwed / Flanged 150#

Glandless Piston Valve - ND40



Size : 1/2" to 4"
MOC : WCB
Seals : Metal To Metal
Pressure : 40Kg/Cm²
Temp. : 4000°C
Ends : DIN 2525 (PN40)

Sengol Exports

F 5 Civil Township Rourkela 769004 india
kausal.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market

GEAR BOX - MANUAL OVER - RIDE CLUTCH - LIMIT SWITCH BOX FOR INDUSTRIAL VALVE

<p>Gear Box for Industrial Valve / Actuator</p>  <p>Torque : 180NM to 35000NM MOC : CI / Ductile Iron / Gun Metal / ALB Travel : 90° (Quarter Turn) Application : Ball Valve, Butterfly Valve & Damper Actuation, Plug valves Operation</p>	<p>Manual over-ride Clutch type for Quarter-turn valves</p>  <p>Torque : 980NM to 3800NM MOC : Cast Iron / Ductile Iron Travel : 90° (Quarter Turn) Application : Gate Valve, Globe Valve & Slide Gate, Open Channel gate valves Operation</p>	<p>Micro Limit Switch Box for Manual Industrial Valve / Pneumatic Actuator</p>  <p>Body : Aluminium Press. Die Cast Switch : 1NO + 1 NC OR 2NO+2NC Enclosure : Weather Proof / Flame Proof Sensors : Micro Switch / Proximity Application : For Feedback of Valve / Dampers at PLC</p>
--	---	---

Y TYPE STRAINER - KNIFE GATE VALVE - CHECK VALVE

<p>Y type Strainer</p>  <p>Size : 1/2" to 12" MOC : WCB / CF8 / CF8M Screen : 40 Mesh / 20 Mesh Seal : NBR Temp. : 220°C Ends : Srewed / Flanged</p>	<p>Knife Gate Valve</p>  <p>Size : 1/2" to 12" MOC : CI/ WCB / CF8 / CF8M Seals : Metal to Metal / NBR/ PTFE Pressure : Upto 2 Kg/cm² (Above on req) Temp. : Upto 80°C / 220°C Ends : Lugged / Flanged type</p>	<p>Check Valve / Non Slam / DPCV</p>  <p>Size : 1/2" to 36" MOC : CI/ WCB / CF8 / CF8M Seals : PTFE / Metal to Metal Pressure : Upto 10kg / Cm² Temp. : Upto 80°C / 220°C Ends : Flanged Type</p>
--	--	---

UPVC / CPVC VALVE

<p>UPVC/CPVC 2 way True Union Ball Valve</p>  <p>Size : 2way-1.1/2" to 4" Body / Ball : UPVC/CPVC Seat : PTFE Stem : UPVC Pressure : 10 BAR Temp. : UP TO 80°C Ends : Socket Type / Srewed End to BSP</p>	<p>UPVC 2 way True Union Ball Valve Flanged end</p>  <p>Size : 2way-1.1/2" to 4" Body / Ball : UPVC/CPVC Seat : PTFE Stem : UPVC Pressure : 10 BAR Temp. : UP TO 80°C Ends : Flanged</p>	<p>UPVC/CPVC 3 Way True Union Ball Valve</p>  <p>Size : 3 way-1/2" to 2" Body / Ball : UPVC/CPVC Seat : PTFE Stem : UPVC Pressure : Up to 7Kg/Cm² Temp. : UP TO 80°C Port : " L " Port Ends : Socket Type / Srewed End to BSP / Flanged End</p>
--	---	---

UPVC / CPVC VALVE

<p>UPVC/CPVC Butterfly Valve For Water Treatment & Plumbing Lines</p>  <p>Size : 2" to 12" Body / Disc : UPVC Seat : EPDM/VITON Pressure : PN 10 Temp. : Up to 80°C Ends : Wafer Type</p>	<p>UPVC Gate Valve</p>  <p>Size : 1 1/2" to 6" Body : UPVC Disc : UPVC/SS 201 Seat : EPDM Pressure : 0.35Mpa Temp. : Up to 60°C Ends : Socket Type</p>	<p>UPVC/CPVC Union Ball Check Valve</p>  <p>Size : 1/2" to 3" Body : UPVC Ball : UPVC Seat : EPDM Pressure : 1.0Mpa (PN10 bar) Temp. : Up to 60°C Ends : Socket Type</p>
--	---	---

Sengol Exports

F 5 Civil Township Rourkela 769004 india
kausal.exports@gmail.com +91-9437047013



Sengol Exports

"Total Solution" from the Indian market



Integral Starter Unit for 3 Phase Electrical Actuator

Torque : Starter Unit Suitable for MOD / ATQ / ATM Series Atuator
Supply : 220V AC / 415V AC
Control : 24V DC / 110V AC /
Signal : 220V AC
Local Switch : Open / Stop / Close / Local & Remote
Lamps : Open / Close / Power / Error



Modulating PCB for Electrical Actuator

Type : PCB suitable for MOD / ATQ / ATM / VO series actuator
Input : 4-20mA / 0-10V DC /
Signal : 5-10V DC
Output : 4-20mA / 0-10V DC /
Signal : 5-10V DC



Position Transmitter Kit (VOT) for Electric Actuator

Type : VOT kit suitable for MOD / ATQ / ATM / VO Series Actuator
Supply : 220V AC / 24V DC (2 Wire)
Output Signal : 4-20 mA / 0-10V DC / 5-10V DC



Fail Safe Module / Battery Backup Unit (BBU)

Type : BBU Unit suitable for MOD / ATQ / ATM / VO Series Actuator
Supply : 220V AC / 24V AC / 24V DC
Function : Determine Open / Closed / Stay put position in case of power failure with the help of BBU.

MOD SERIES

Single Phase Quarter Turn



SUPPLY VOLTAGE
 220 V AC (± 10%), 50 / 60 Hz
 110 V AC,
 24V DC, 12 V DC
ENCLOSURE - IP 67/68
 Weatherproof
 IS / IEC 60529
 Flameproof or Ex-Proof - IS
 IEC 60079
 Zone II, Gas Group IIB T4
TORQUE RANGE
 15 Nm to 5000 Nm

ATQ SERIES

Three Phase Quarter Turn



SUPPLY VOLTAGE
 415 V AC (± 10%), 50 / 60 Hz
 380 V AC
 460V AC
ENCLOSURE - IP 67/68
 Weatherproof
 IS / IEC 60529
 Flameproof or Ex-Proof - IS
 IEC 60079
 Zone II, Gas Group IIB T4
TORQUE RANGE
 50 Nm to 12000 Nm

ATM SERIES

Three Phase Multi-Turn



SUPPLY VOLTAGE
 415 V AC (± 10%), 50 / 60 Hz
 380 V AC / 460V AC
 220 V AC CTM Series
ENCLOSURE - IP 67/68
 Weatherproof
 IS / IEC 60529
 Flameproof or Ex-Proof - IS
 IEC 60079
 Zone II, Gas Group IIB T4
TORQUE RANGE
 50 Nm to 2400 Nm

VO SERIES

Single Phase Linear



SUPPLY VOLTAGE
 220 V AC (± 10%), 50 / 60 Hz
 110 V AC, 24 V DC, 12V DC
 (Available On request)
ENCLOSURE - IP 67
 Weatherproof - IS / IEC 60529
TORQUE RANGE
 150 Kgf to 3500 Kgf

Sengol Exports

F 5 Civil Township Rourkela 769004 india
kausol.exports@gmail.com +91-9437047013